

5      Claims

I claim:

1.      A door holder door stop to secure a door in an open position adjacent a wall,  
10      said door holder door stop comprising:  
         an elongated arm having a first end and a second end,  
         first attaching means for securing the second end of the elongated arm to the  
         wall,  
         a magnetic head attached at the second end of the elongated arm, said  
15      magnetic head having a magnetic surface, wherein the magnetic head longitudinally  
         extends from the surface of the wall,  
         a metal plate having a first side and a second side,  
         second attaching means for attaching said second side of the plate to the door,  
         wherein the magnetic head is secured to the first side of the plate by a magnetic  
20      force of attraction to hold the door in an open position when the door is opened,  
         wherein the magnetic head and the magnetic surface each having a  
         circumference in alignment with the circumference of the first end of the arm.
2.      The door holder door stop as recited in Claim 1, wherein the magnetic surface  
         has a flat surface.
- 25      3.      The door holder door stop as recited in Claim 1, wherein the first side and the  
         second side of the plate each having a flat surface.
4.      The door holder door stop as recited in Claim 1, wherein the second side of the  
         plate having an adhesive surface to fixedly secure the metal plate to the door.
5.      The door holder door stop as recited in Claim 1, wherein the first attaching  
30      means comprising a screw disposed at the second end of the elongated arm.
6.      The door holder door stop as recited in Claim 1, wherein the magnetic force is  
         broken by pulling the door such that the plate and the arm are separated.
7.      The door holder door stop as recited in Claim 1, wherein the plate having a  
         rectangular configuration.

- 5        8.        The door holder door stop as recited in Claim 5, wherein the screw has a threaded outside wall.
9.        A door holder door stop to secure a door in an open position adjacent a wall, said door holder door stop comprising:
- 10            an elongated arm having a first end and a second end,
- first attaching means for securing the second end of the elongated arm to the wall,
- a magnetic head attached at the second end of the elongated arm, said magnetic head having a magnetic surface,
- a plate having a first side and a second side,
- 15            second attaching means for attaching said second side of the plate to the door.
10.        The door holder door stop as recited in Claim 9, wherein the magnetic surface has a flat surface.
11.        The door holder door stop as recited in Claim 9, wherein the first side and the second side of the plate each having a flat surface.
- 20        12.        The door holder door stop as recited in Claim 9, wherein the second side of the plate having an adhesive surface to fixedly secure the metal plate to the door.
13.        The door holder door stop as recited in Claim 9, wherein the first attaching means comprising a screw disposed at the second end of the elongated arm.
14.        The door holder door stop as recited in Claim 9, wherein the first side of the plate
- 25        is constructed of metal.
15.        The door holder door stop as recited in Claim 14, wherein the magnetic head is secured to the first side of the plate by a magnetic force of attraction to hold the door in an open position when the door is opened.
16.        The door holder door stop as recited in Claim 15, wherein the magnetic force is
- 30        broken by pulling the door such that the plate and the arm are separated.
17.        The door holder door stop as recited in Claim 9, wherein the magnetic surface having a circumference in alignment with the circumference of the first end of the arm.
18.        The door holder door stop as recited in Claim 17, wherein the magnetic surface having a circumference in alignment with the circumference of the magnetic head.

5      19.    The door holder door stop as recited in Claim 9, wherein the plate having a rectangular configuration.

20.    The door holder door stop as recited in Claim 9, wherein the magnetic head longitudinally extends from the surface of the wall.

10      21.    The door holder door stop as recited in Claim 13, wherein the screw has a threaded outside wall.

15

20

25

30